Well Construction

AEON

Foam Wiper Balls

The foam wiper ball is designed to wipe the drill pipe or tubing string clean of cement, fluids or debris and can also be used to separate fluids.

Manufactured from natural rubber with a high parting stretch of 380 to 440% means that the ball can pass through small restrictions without being damaged. This allows for easy passage through internal upsets or restrictions such as mechanical setting tools, running tools and diverters.

The foam wiper ball range are suitable for use across a range of temperatures from 40°F to 302°F and have been used with all types of drilling and displacement fluids.



Specifications

Part number	Actual size	Typical wiping range	Minimum restriction
CX02FWB	2.36"	1.95" to 0.85"	0.400"
CX03FWB	3.14"	2.50" to 1.10"	0.482"
CX04FWB	3.94"	3.12" to 1.38"	0.625"
CX05FWB	4.72"	4.00" to 1.75"	0.765"
CX06FWB	5.92"	4.75" to 2.00"	0.875"
CX07FWB	6.89"	5.50" to 2.38"	1.000"
CX08FWB	7.87"	7.00" to 3.00"	1.321"
CX12FWB	11.81"	9.50" to 4.10"	1.875"

Copyright 2026 Expro. All Rights Reserved. Notice: this product is protected by one or more patents assigned to Expro or one of its affiliated entities. For more information regarding Expro's patents, please go to: www.expro.com/patents. The sale, rental and use of Expro's products and the offering of services are subject to Expro's standard terms and conditions, available on request. Unless noted otherwise, trademarks and service marks herein are the property of Expro. Product and service information and/or specifications are subject to change without notice. For more information, please contact an authorized Expro representative.