Well Construction

Conductor Driving and Slot Recovery

Guillotine Pipe Saw

Expro's Guillotine Pipe Saw is used to cut through cemented casing strings.



Features and benefits

- Time saving
- Cold cut process, no need for a how work permit
- Can be run remotely
- Can be utilized underwater

Applications

- Pipe recovery operations
- Decommissioning operations

Specifications	
Pipe mounting diameters	16" to 32" (41mm to 81mm)
Required power source	Standard: 15 gpm @ 1,500 psi 57 L/m @ 103 bar Autoclamp: 15 gpm @ 2,000 psi 57 L/m @ 138 bar
Autofeed rate (per cycle)	Low Speed: 0.008" (0.020 cm) High Speed: 0.016" (0.041 cm)
Dimensions (standard)	Length: 76.5" (194 cm) Width: 66" (168 cm) Height: 25" (63.5 cm)
Dimensions (Autoclamp)	Length: 82.5" (210 cm) Width: 78" (198 cm) Height: 25.9" (65.8 cm)
Weight	Standard: 1,800 lbs (818 kg) Autoclamp: 2,100 lbs (955 kg)





FRANK'S TUBULAR RUNNING SERVICES

expro.com/frankstrs

Date 10/2026 | Revision 2.0

Copyright 2026 Expro. All Rights Reserved. Notice: this product is protected by one or more patents assigned to Expro or one of its affiliated entities. For more information regarding Expro's patents, please go to: www.expro. com/patents. The sale, rental and use of Expro's products and the offering of services are subject to Expro's standard terms and conditions, available on request. Unless noted otherwise, trademarks and service marks herein are the property of Expro. Product and service information and/or specifications are subject to change without notice. For more information, please contact an authorized Expro representative.