

EXTENDED RANGE™ Split Bushing Spider

1,250 & 1,000 Ton



Key Benefits and Features

- The first casing spider available to the industry with a safe-working load rating greater than 1,000 tons
- Available in 1,250 and 1,000 ton
- Centers pipe automatically without the need for an external centering device
- Tapered casing strings can be run with little or no adjustments and without changing slips

Use in the following applications:

Deepwater and ultra-deepwater

Shelf

Land

The unique design of Frank's EXTENDED RANGE™ Split Bushing Spider allows the tool to grip casing with improved resistance to slip crushing in comparison to standard casing tools.

Our Spider/Elevator Interlock System ensures that either the spider or the elevator is properly set on the pipe before the companion tool is allowed to open.

The spider's custom design centers pipe automatically without the need for an external centering device. Hydraulic slip actuation ensures the slips are set.

Slips open to provide a passage which is 5 inches in diameter over the nominal pipe size for which the tool is dressed. For example, with the spider dressed for 20 inch casing, the passage through the open slips is 25 inches in diameter.

Tapered casing strings can be run with little or no adjustments and without changing slips.



22 inch x 1250 Ton Split Bushing Spider

Specifications

Model	Weight	Dimensions			Rotary Table	Pipe Range	Rated Capacity
		Into Rotary	Above Rig Floor	O.D.			
22 inch – 1,250-ton	11,115 pounds (dressed for 17")	20 7/8 inches	8 7/8 inches	52 1/2 inches	49 1/2 inches	11 3/4 – 22 inches	1,250 tons
14 inch – 1,000-ton	5,788 pounds (dressed for 14")	22 inches	5 3/4 inches	40 inches	37 1/2 inches	4 1/2 – 14 inches	1,000 tons
30 inch – 1,000-ton	7,800 pounds (dressed for 30")	23 inches	9 1/8 inches	52 1/2 inches	49 1/2 inches	24 – 30 inches	1,000 tons

franksinternational.com

For more information call 1-800-833-7265

©2017 Frank's International. All Rights Reserved. Notice: this product is protected by one or more patents. For more information regarding Frank's International's patents, please go to: www.franksinternational.com/patents/. Frank's International products and services are subject to the Company's standard terms and conditions, available on request. Unless noted otherwise, trademarks and service marks herein are the property of Frank's International. Product and service information and/or specifications are subject to change without notice. For more information please contact an authorized Frank's International representative.