

TAD-1 Retrievable Tension Packer

Key Benefits and Features

- Incorporates three release methods to ensure successful retrieval operations
- Rocker-type slip design provides well integrity during zonal isolation operations
- One-piece, field proven packing element system ensures reliable seal integrity during downhole operations



Use in the following applications:

Shelf

Land

TAD-1 Retrievable Tension Packers provide a compact, economical retrievable packer option when compression set packers are impractical due to pressure requirements. The TAD-1 Retrievable Tension Packer can be utilized in most low-pressure production, water injection, and pressure work applications.

Specifications

Casing OD (IN.)	Casing Weight Range (LBS/FT)	Casing Min ID Setting Range (IN.)	Casing Max ID Setting Range (IN.)	Gauge Ring OD (IN.)	Thread Connection	Maximum Operating Temperature (°F)
5-1/2	15.5-20	4.778	4.95	4.641	2-3/8 EUE	250
	13.0-17.0	4.892	5.044	4.75	2-3/8 EUE	250
7	32.0-35.0	6.044	6.094	5.812	2-3/8 EUE	250
	26.0-29.0	6.184	6.276	5.968	2-3/8 EUE	250
	23-29	6.184	6.276	5.968	2-3/8 EUE 4-1/2 LTC	250
	20.0-26.0	6.276	6.456	6.078	2-7/8 EUE	250
7-5/8	33.7-39.0	6.625	6.765	6.453	2-7/8 8 RD	250
	24.0-29.7	6.875	7.025	6.672	2-7/8 8 RD	250
9-5/8	47.0-53.5	8.535	8.681	8.218	3-1/2 EUE 4-1/2 LTC	250
	40.0-47.0	8.681	8.835	8.437	3-1/2 EUE	250
	29.3-36.0	8.921	9.063	8.593	3-1/2 EUE	250
10 3/4	32.7-55.5	9.625	10.192	9.500	3-1/2 EUE	250
11 3/4	38-60	10.605	11.2	10.5	3-1/2 EUE	250
13 3/8	48-72	12.300	12.715	12.000	3-1/2 EUE	250